NSN 5305-01-197-6514

Between 0.515 inches and 0.555 inches

Between 1.463 inches and 1.483 inches

Thread Class:

Right-hand

Thread Length:

Thread Direction:

Fastener Length:

Head Style: Pan no. 2

Head Diameter:

За

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-197-6514

Between 0.477 inches and 0.492 inches
Head Height:
Between 0.140 inches and 0.150 inches
Grip Diameter:
Between 0.2490 inches and 0.2495 inches
Internal Drive Style:
Double hexagon
Thread Diameter:
0.250 inches
Grip Length:
Between 0.928 inches and 0.948 inches
Width Across Flats:
Between 0.1565 inches and 0.1587 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Surface Finish:
32.0 microinches threads
Special Features:
Ream for press fit with plug, 3slots
Material:
Iron alloy 660
Material Specification:
Ams 5732 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf

NSN 5305-01-197-6514

Close Tolerance Screw - Page 2 of 2



	Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0