NSN 5305-01-197-6566

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-197-6566 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.313 inches **Fastener Length:** 0.875 inches **Head Style:** Hexagon **Head Height:** 0.250 inches Width Between Flats: 0.562 inches **First Diameter From Head:** 0.270 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.562 inches **Point Style:** Flat **Internal Drive Style:** Slot **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): 16 **Externally Relieved Body Diameter Quantity:** Material: Copper alloy 210 or copper alloy 230 or copper alloy 240 or copper alloy 260 or copper alloy 268 or copper alloy 342 or copper alloy 353 **Material Specification:** Astm b36 assn standard single material response or astm b 121 assn standard single material response **Thread Series Designator:** Unc **Specification Data:** 81349-mil-e-24142 government specification Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5305-01-197-6566

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0