NSN 5305-01-197-6567

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-197-6567 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 1.500 inches **Fastener Length:** 5.100 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.218 inches and 0.226 inches **Head Height:** Between 0.134 inches and 0.138 inches **Shank Unthreaded Hole Diameter:** 0.060 inches first hole and 0.065 inches first hole First Diameter From Head: Between 0.1045 inches and 0.1075 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.018 inches and 0.020 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.138 inches Width Across Flats: Between 0.109 inches and 0.111 inches Thready Qty Per Inch (tpi): Distance From Head Largest Bearing Surface To Shank Hole Center: 5.000 inches first hole **Externally Relieved Body Diameter Quantity:** Material: Steel comp 303 **Material Specification:** Qq-s-764 cond a federal specification single material response **Surface Treatment: Passivate Thread Series Designator:** Unc Shelf Life:

N/a

NSN 5305-01-197-6567

Externally Relieved Body Screw - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0