

View Online at <https://aerobasegroup.com/nsn/5305-01-197-6612>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.444 inches and 0.494 inches

**Fastener Length:**

Between 1.204 inches and 1.234 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.497 inches and 0.507 inches

**Grip Diameter:**

Between 0.2490 inches and 0.2495 inches

**Internal Drive Style:**

High-torque

**Thread Diameter:**

0.250 inches

**Grip Length:**

Between 0.740 inches and 0.760 inches

**Thready Qty Per Inch (tpi):**

28

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Special Features:**

Tapped hole in head 0.1380-32, unjc-3b threads. Distance from top of head to injection port 0.450 inch. Injection port 0.120 in. Lg, 0.060 in.

Wide

**Material:**

Titanium alloy

**Material Specification:**

Ams 4928 assn standard single material response or ams 4967, comp 6al-4v assn standard single material response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0