NSN 5305-01-197-6820

Close Tolerance Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-197-6820

3a Thread Direction: Right-hand Thread Length: 0.370 inches Fastener Length: Between 0.793 inches and 0.823 inches Head Style: Pan no. 2 Head Diameter: Between 0.456 inches and 0.508 inches Head Height: 0.111 inches
Right-hand Thread Length: 0.370 inches Fastener Length: Between 0.793 inches and 0.823 inches Head Style: Pan no. 2 Head Diameter: Between 0.456 inches and 0.508 inches Head Height:
Thread Length: 0.370 inches Fastener Length: Between 0.793 inches and 0.823 inches Head Style: Pan no. 2 Head Diameter: Between 0.456 inches and 0.508 inches Head Height:
0.370 inches Fastener Length: Between 0.793 inches and 0.823 inches Head Style: Pan no. 2 Head Diameter: Between 0.456 inches and 0.508 inches Head Height:
Fastener Length: Between 0.793 inches and 0.823 inches Head Style: Pan no. 2 Head Diameter: Between 0.456 inches and 0.508 inches Head Height:
Between 0.793 inches and 0.823 inches Head Style: Pan no. 2 Head Diameter: Between 0.456 inches and 0.508 inches Head Height:
Head Style: Pan no. 2 Head Diameter: Between 0.456 inches and 0.508 inches Head Height:
Pan no. 2 Head Diameter: Between 0.456 inches and 0.508 inches Head Height:
Head Diameter: Between 0.456 inches and 0.508 inches Head Height:
Between 0.456 inches and 0.508 inches Head Height:
Head Height:
-
0.111 inches
Grip Diameter:
Between 0.2490 inches and 0.2495 inches
Internal Drive Style:
Tri-wing recess
Thread Diameter:
0.250 inches
Grip Length:
Between 0.428 inches and 0.448 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Material:
Steel comp 3140
Thread Series Designator:
Unjf
Specification Data:
80205-nas4600 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0