NSN 5305-01-197-9413

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-197-9413 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.300 inches and 0.380 inches **Fastener Length:** Between 0.350 inches and 0.380 inches **Head Style:** Pan **Head Diameter:** Between 0.205 inches and 0.219 inches **Head Height:** Between 0.070 inches and 0.080 inches **Locking Feature:** Strip threads or patch threads or pellet threads **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch **Surface Finish:** 63.0 microinches bearing surface of head **Product Name:** Navy special project Material: Steel comp 4140 or steel comp 4340 or steel comp 8740 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response **Thread Series Designator:** Unjc **Specification Data:** 80205-nas8000 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:**

--

NSN 5305-01-197-9413

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0