NSN 5305-01-197-9427

Close Tolerance Screw - Page 1 of 2

3a

24





Thread Class: Thread Direction: Right-hand Thread Length: Between 0.454 inches and 0.521 inches Fastener Length: Between 1.402 inches and 1.449 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.578 inches and 0.634 inches **Grip Diameter:** Between 0.3110 inches and 0.3120 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.312 inches Grip Length: Between 0.928 inches and 0.948 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 220000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads **Product Name:** Navy special project **Special Features:** Internal drive ribbed Material: Steel comp h11 **Material Specification:** Ams6487 assn standard single material response **Surface Treatment:** Cadmium or cadmium and chromate **Surface Treatment Specification:** Nas672 assn standard 1st treatment response or mil-c-8837, ty2, cl2 military specification 2nd treatment response **Thread Series Designator:**

Unjf

NSN 5305-01-197-9427

Close Tolerance Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.

