NSN 5305-01-198-3482

Thread Class:

Thread Direction:

За

N/a

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-198-3482

Right-hand						
Thread Length:						
Between 0.291 inches and 0.341 inches						
Fastener Length:						
Between 1.239 inches and 1.269 inches						
Head Style:						
Flat chamfer						
Head Diameter:						
Between 0.365 inches and 0.375 inches						
Head Height:						
Between 0.133 inches and 0.150 inches						
Grip Diameter:						
Between 0.2485 inches and 0.2495 inches						
Internal Drive Style:						
Offset cruciform (torque set)						
Thread Diameter:						
0.250 inches						
Grip Length:						
Between 0.928 inches and 0.948 inches						
Thready Qty Per Inch (tpi):						
Thready Qty Per Inch (tpi):						
Thready Qty Per Inch (tpi): 28						
28						
28 Min. Tensile Strength (psi):						
28 Min. Tensile Strength (psi): 160000 pounds per square inch						
28 Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish:						
28 Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads						
Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Material:						
Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660						
Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification:						
Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response						
Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response Surface Treatment:						
Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response Surface Treatment: Passivate						
Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification:						
Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response						
Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator:						
Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjf						

NSN 5305-01-198-3482

Close Tolerance Screw - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0