

View Online at <https://aerobasegroup.com/nsn/5305-01-198-4152>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.528 inches and 0.620 inches

**Fastener Length:**

Between 0.590 inches and 0.620 inches

**Head Style:**

Pan

**Head Diameter:**

Between 0.367 inches and 0.373 inches

**Head Height:**

Between 0.122 inches and 0.133 inches

**Locking Feature:**

Strip threads or patch threads or pellet threads

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

32

**Surface Finish:**

63.0 microinches bearing surface of head

**Material:**

Steel comp 4140 or steel comp 4340 or steel comp 8740

**Material Specification:**

Mil-s-5626 military specification 1st material response or ams6414 assn standard 2nd material response or mil-s-8844 military specification 2nd material response or mil-s-6049 military specification 3rd material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, ty2, cl2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas8003 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5626 spec.