NSN 5305-01-198-4153

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-198-4153 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.408 inches and 0.500 inches **Fastener Length:** Between 0.470 inches and 0.500 inches **Head Style:** Pan **Head Diameter:** Between 0.367 inches and 0.373 inches **Head Height:** Between 0.122 inches and 0.133 inches **Locking Feature:** Strip threads or patch threads or pellet threads **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 **Surface Finish:** 63.0 microinches bearing surface of head **Product Name:** Navy special project Material: Steel comp 4140 or steel comp 4340 or steel comp 8740 **Material Specification:** Mil-s-5626 military specification 1st material response or ams6414 assn standard 2nd material response or mil-s-8844 military specification 2nd material response or mil-s-6049 military specification 3rd material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-4166, ty2, cl2 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas8003 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

NSN 5305-01-198-4153

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.