NSN 5305-01-198-8059

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-198-8059 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.864 inches **Fastener Length:** 2.050 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 1.160 inches and 1.170 inches **Head Height:** 0.150 inches **First Diameter From Head:** Between 0.6860 inches and 0.6865 inches **Second Diameter From Head:** Between 0.529 inches and 0.539 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 1.088 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 1.225 inches and 1.240 inches **Point Style:** Flat **Internal Drive Style:** High-torque **Thread Diameter:** 0.625 inches Thready Qty Per Inch (tpi): 18 **Countersink Angle:** 101.0 degrees **Externally Relieved Body Diameter Quantity:** 2 **Special Features:** It has a concentric threaded hole along the longitudinal centerline, 0.50020 unjf-3b, 0.943 in. Deep Material: Steel comp xm-13 **Material Specification:** Astm 5629 assn standard single material response

Unjf

Thread Series Designator:

NSN 5305-01-198-8059

Externally Relieved Body Screw - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0