

View Online at <https://aerobasegroup.com/nsn/5305-01-198-8532>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.170 inches and 0.190 inches

Fastener Length:

Between 0.610 inches and 0.630 inches

Head Style:

Pan

Head Diameter:

Between 0.205 inches and 0.219 inches

Head Height:

Between 0.070 inches and 0.080 inches

First Diameter From Head:

Between 0.075 inches and 0.085 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.435 inches and 0.445 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.112 inches

Thready Qty Per Inch (tpi):

40

Externally Relieved Body Diameter Quantity:

1

Material:

Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385 or steel comp 303 or steel comp 303se

Surface Treatment:

Oxide

Surface Treatment Specification:

Mil-c-13924, cl2 military specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.