NSN 5305-01-199-1339

Close Tolerance Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-199-1339

| view Online at https://aerobasegroup.com/nsi/0500-01-199-1559 |
|--|
| Thread Class: |
| За |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.323 inches |
| Fastener Length: |
| Between 1.246 inches and 1.276 inches |
| Head Style: |
| Pan no. 2 |
| Head Diameter: |
| Between 0.357 inches and 0.373 inches |
| Head Height: |
| Between 0.103 inches and 0.118 inches |
| Grip Diameter: |
| Between 0.1890 inches and 0.1895 inches |
| Internal Drive Style: |
| Tri-wing recess |
| Thread Diameter: |
| 0.190 inches |
| Grip Length: |
| Between 0.928 inches and 0.948 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Material: |
| Titanium alloy |
| Material Specification: |
| Ams4928 assn standard single material response or ams4967 assn standard single material response |
| Thread Series Designator: |
| Unjf |
| Specification Data: |
| 80205-nas5203 professional/industrial association standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Filg: |
| A003b0 |