## NSN 5305-01-199-2287

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-199-2287 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.338 inches and 0.388 inches **Fastener Length:** Between 0.848 inches and 0.878 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.2578 inches and 0.3047 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.490 inches and 0.510 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Surface Finish:** 32.0 microinches threads **Special Features:** Internal drive ribbed Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1581 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5305-01-199-2287

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0