NSN 5305-01-199-7853

Close Tolerance Screw - Page 1 of 2

3a

24





Thread Class: Thread Direction: Right-hand Thread Length: Between 0.476 inches and 0.526 inches Fastener Length: Between 2.736 inches and 2.766 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.578 inches and 0.633 inches **Grip Diameter:** Between 0.3110 inches and 0.3120 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.312 inches Grip Length: Between 2.240 inches and 2.260 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, cl 2 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1580 professional/industrial association standard Shelf Life:

N/a

NSN 5305-01-199-7853

Close Tolerance Screw - Page 2 of 2

AeroBase Group

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0