NSN 5305-01-200-1433

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-200-1433 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.355 inches and 0.385 inches **Fastener Length:** Between 1.235 inches and 1.255 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.364 inches and 0.397 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **Internal Drive Style:** Cross recess type 1 **End Application:** Aircraft, stratolifter c-135 **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.870 inches and 0.880 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 95000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Titanium alloy **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Aluminum **Surface Treatment Specification:** Bms10-85 type 1, fscm 81205 mfr ref single treatment response **Thread Series Designator:** Unf Shelf Life: N/a

--

Unit Of Measure:

NSN 5305-01-200-1433

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0