NSN 5305-01-200-1434

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-200-1434

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.355 inches and 0.385 inches
Fastener Length:
Between 0.913 inches and 0.953 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.364 inches and 0.397 inches
Grip Diameter:
Between 0.2485 inches and 0.2495 inches
Internal Drive Style:
Cross recess type 1
End Application:
Aircraft, stratolifter c-135
Thread Diameter:
0.250 inches
Grip Length:
Between 0.558 inches and 0.568 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
95000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Material:
Titanium alloy
Material Specification:
Ams 4928 assn standard single material response or ams 4967 assn standard single material response
Surface Treatment:
Aluminum
Surface Treatment Specification:
Bms 10-85, type 1, fscm 81205 mfr ref single treatment response
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5305-01-200-1434

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0