NSN 5305-01-200-1436



Panel Screw Assembly - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5305-01-200-1436 **Thread Class:** За **Thread Direction:** Right-hand **Fastener Length:** Between 0.340 inches and 0.370 inches **Head Style:** Knurled no. 4 **Head Diameter:** Between 0.370 inches and 0.400 inches **Head Height:** Between 0.341 inches and 0.371 inches **Internal Drive Style:** Cross recess type 1 **Material Accommodated Thickness:** Between 0.032 inches and 0.093 inches **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 Material: Steel comp xm-7 fastener or steel comp 302 fastener or steel comp 304 fastener or steel comp 305 fastener or steel comp 316 fastener or steel comp 305 fastener or steel comp 306 fastener or steel comp 307 fastener or steel comp 308 faste steel comp 321 fastener or steel comp 347 fastener or steel comp 384 fastener or steel comp 385 fastener **Material Specification:** Qq-w-423, cond b federal specification single material response spring **Surface Treatment:** Passivate spring **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response spring **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** Demilitarization: No Fiig: A003b0

Mil-s-5059 spec.

Mil-std (military Standard):