NSN 5305-01-200-2758

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-200-2758

Thread Class.
Thread Class:
3a Thread Direction:
Right-hand
Fastener Length:
Between 1.090 inches and 1.150 inches
Head Style: Fillister
Head Diameter:
Between 0.550 inches and 0.562 inches
Head Height:
Between 0.368 inches and 0.375 inches
Hole Diameter:
Between 0.061 inches and 0.067 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.375 inches
Width Across Flats:
0.3125 inches
Hole Quantity:
6 =
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
16
Min. Tensile Strength (psi):
130000 pounds per square inch
Minimum Yield Strength:
90000 pounds per square inch
Hole Configuration Style:
Hexagon flats
Criticality Code Justification:
Zzzy
Material:
Nickel alloy k-500
Material Specification:
Qq-n-286 class a federal specification single material response
Thread Series Designator:
Unc

Reference Number Differentiating Characteristics:

Quality control iaw navships 0948-045-7010 material identification and control instruction for level 1 items

NSN 5305-01-200-2758

Socket Head Cap Screw - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0