## NSN 5305-01-200-7730

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-200-7730 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.750 inches **Fastener Length:** 1.270 inches **Head Style:** Hexagon **Head Height:** 0.210 inches Width Between Flats: 0.563 inches **First Diameter From Head:** 0.262 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.520 inches **Internal Drive Style:** W/o internal drive **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): 16 Hardness Rating: 33.0 rockwell c and 39.0 rockwell c **Externally Relieved Body Diameter Quantity:** Material: Steel comp 4140 or steel comp 8640 **Material Specification:** Astm-a322 assn standard 1st material response or astm-a331 assn standard 2nd material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416 type 2 class 3 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

--

## NSN 5305-01-200-7730

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0