## NSN 5305-01-200-7732



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-200-7732 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.357 inches and 0.438 inches **Fastener Length:** Between 0.407 inches and 0.438 inches **Head Style:** Pan **Head Diameter:** Between 0.256 inches and 0.270 inches **Head Height:** Between 0.087 inches and 0.097 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 80000 pounds per square inch **Screw Material:** Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 **Screw Surface Treatment:** Oxide **Screw Surface Treatment Specification:** Mil-c-13924, cl 4 military specification single treatment response Color: Black **Thread Series Designator: Specification Or Standard:** 3 type and 9c style Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No Fiig: A500d0

## NSN 5305-01-200-7732

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-c-13924 spec.