## NSN 5305-01-200-9871

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-200-9871

| Thread Class:  |
|--|
|  |
| 2a   |
| Thread Direction:  |
| Right-hand   |
| Thread Length:   |
| Between 0.761 inches and 0.875 inches                                  |
| Fastener Length:   |
| Between 0.844 inches and 0.875 inches                                  |
| Head Style:  |
| Fillister  |
| Head Diameter:   |
| Between 0.292 inches and 0.313 inches                                  |
| Head Height:   |
| Between 0.123 inches and 0.130 inches                                  |
| Hole Diameter:   |
| Between 0.045 inches and 0.050 inches                                  |
| Internal Drive Style:  |
| Slot   |
| Thread Diameter:   |
| 0.190 inches   |
| Hole Quantity:   |
| 1  |
| Thready Qty Per Inch (tpi):  |
| 24   |
| Screw Material:  |
| Steel comp 302 or steel comp 304 or steel comp 316 or steel comp 303se |
| Screw Material Specification:  |
| 66 federal standard all material responses                             |
| Screw Surface Treatment:   |
| Passivate  |
| Screw Surface Treatment Specification:                                 |
| Qq-p-35 federal specification single treatment response                |
| Head Hole Configuration Style:   |
| Round  |
| Thread Series Designator:  |
| Unc  |
| Specification Or Standard:   |
| 3 type and 4c style  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |

--

## NSN 5305-01-200-9871

Machine Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A500d0