

View Online at <https://aerobasegroup.com/nsn/5305-01-200-9872>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.773 inches and 0.875 inches

**Fastener Length:**

Between 0.844 inches and 0.875 inches

**Head Style:**

Fillister

**Head Diameter:**

Between 0.389 inches and 0.414 inches

**Head Height:**

Between 0.161 inches and 0.170 inches

**Hole Diameter:**

0.062 inches

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.250 inches

**Hole Quantity:**

1

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

57000 pounds per square inch

**Screw Material:**

Copper alloy 230 or copper alloy 240 or copper alloy 260 or copper alloy 268 or copper alloy 270 or copper alloy 342 or copper alloy 353 or copper alloy 360 or copper alloy 377 or copper alloy 462 or copper alloy 464 or copper alloy 482 or copper alloy 485 or copper alloy 510 or copper alloy 745 or copper alloy 752 or copper alloy 764 or copper alloy 770

**Head Hole Configuration Style:**

Round

**Thread Series Designator:**

Unf

**Specification Or Standard:**

1 type and 8s style

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0