

View Online at <https://aerobasegroup.com/nsn/5305-01-201-2238>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 1.750 inches and 1.938 inches

Fastener Length:

Between 4.906 inches and 5.000 inches

Head Style:

Hexagon

Head Height:

Between 0.455 inches and 0.483 inches

Width Between Flats:

Between 1.100 inches and 1.125 inches

Hole Diameter:

Between 0.092 inches and 0.100 inches

Thread Diameter:

0.750 inches

Hole Quantity:

1

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

16

Min. Tensile Strength (psi):

90000 pounds per square inch

Hardness Rating:

235.0 brinell standard

Minimum Yield Strength:

40000 pounds per square inch

Hole Configuration Style:

Hexagon longitudinal hole

Special Features:

Provided with snap ring groove and graphite lube mil-I-8937

Material:

Steel comp 403 or steel comp 410 or steel comp 416 or steel comp 420 or steel comp 429 or steel comp 4340 or steel comp 440a or steel comp 440b or steel comp 440c or steel comp 440fse or steel comp 446

Material Specification:

66 federal standard all material responses

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0