

View Online at <https://aerobasegroup.com/nsn/5305-01-201-4848>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.304 inches and 0.307 inches

**Fastener Length:**

0.382 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

0.375 inches

**Head Height:**

0.125 inches

**First Diameter From Head:**

0.188 inches

**Second Diameter From Head:**

Between 0.071 inches and 0.074 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

0.070 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

Between 0.075 inches and 0.078 inches

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.112 inches

**Thready Qty Per Inch (tpi):**

40

**Askewed Head Angle:**

45.0 degrees

**Externally Relieved Body Diameter Quantity:**

2

**Material:**

Steel comp 303

**Material Specification:**

Astm a-582 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Mil-std-171 military specification single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-std-171 spec.