Socket Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-201-9383



Thread Class: 3a **Thread Direction: Right-hand Thread Length:** Between 0.594 inches and 0.750 inches Fastener Length: Between 0.719 inches and 0.750 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.550 inches and 0.562 inches **Head Height:** Between 0.368 inches and 0.375 inches Locking Feature: Patch threads or strip threads **Internal Drive Style:** Hexagon **Thread Diameter:** 0.375 inches Width Across Flats: Between 0.3125 inches and 0.3160 inches Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 170000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c **Minimum Yield Strength:** 150000 pounds per square inch Surface Finish: 63.0 microinches bearing surface of head Material: Steel **Material Specification:** 66 federal standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2 class 3 federal specification single treatment response **Thread Series Designator:**

Unc

NSN 5305-01-201-9383

Socket Head Cap Screw - Page 2 of 2

Specification Or Standard:

6 type

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

