## NSN 5305-01-202-2027

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-202-2027 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.210 inches **Fastener Length:** 0.348 inches **Head Style:** Hexagon **Head Height:** 0.090 inches Width Between Flats: 0.438 inches **Shoulder Diameter:** 0.240 inches first shoulder and 0.245 inches first shoulder **Shoulder Length:** 0.078 inches first shoulder **Internal Drive Style:** W/o internal drive **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 **Shoulder Shape:** Round first shoulder **Special Features:** Undercut between shoulder and thread length of 0.060 in. Nom. Length and 0.094 in. Nom. Dia. Material: Steel comp 304 **Material Specification:** Astm a582, cond a assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5305-01-202-2027

Shoulder Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0