

View Online at <https://aerobasegroup.com/nsn/5305-01-202-2672>

**Thread Direction:**

Right-hand

**Thread Length:**

Between 8.6 millimeters and 10.0 millimeters

**Fastener Length:**

10.00 millimeters

**Head Style:**

Pan

**Head Diameter:**

Between 7.44 millimeters and 7.80 millimeters

**Head Height:**

Between 2.55 millimeters and 2.80 millimeters

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

4.0 millimeters

**Min. Tensile Strength (psi):**

80000 pounds per square inch

**Thread Pitch In Millimeters:**

0.7

**External Thread Tolerance Class:**

6g

**Screw Material:**

Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385 or steel comp 303 plus x or steel comp 303ma or steel comp 303cu

**Screw Surface Treatment:**

Oxide

**Screw Surface Treatment Specification:**

Mil-c-13924 class 4 military specification single treatment response

**Color:**

Black

**Thread Series Designator:**

M

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0

**Mil-std (military Standard):**

Mil-c-13924 spec