NSN 5305-01-202-2679

Close Tolerance Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-202-2679



Thread Class: 3a **Thread Direction: Right-hand Thread Length:** Between 0.378 inches and 0.428 inches Fastener Length: Between 0.700 inches and 0.730 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.477 inches and 0.492 inches **Head Height:** Between 0.140 inches and 0.150 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.250 inches Grip Length: Between 0.302 inches and 0.322 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads **Special Features:** Internal drive ribbed Material: Iron alloy 660 **Material Specification:** Ams 5731 assn standard single material response or ams 5732 assn standard single material response Surface Treatment: Passivate **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1578 professional/industrial association standard

NSN 5305-01-202-2679

Close Tolerance Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

