## NSN 5305-01-202-3414

Close Tolerance Screw - Page 1 of 2



view Online at https://aerobasegroup.com/hsn/5505-01-202-5414
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.476 inches and 0.526 inches
Fastener Length:
Between 1.048 inches and 1.078 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.5780 inches and 0.6335 inches
Grip Diameter:
Between 0.3110 inches and 0.3120 inches
Internal Drive Style:
High-torque
Thread Diameter:
0.312 inches
Grip Length:
Between 0.552 inches and 0.572 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Surface Finish:
32.0 microinches threads
Material:
Iron alloy 660
Material Specification:
Ams5731 assn standard single material response or ams5732 assn standard single material response or ams5737 assn standard single
material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf

**Specification Data:** 

80205-nas1580 professional/industrial association standard

## NSN 5305-01-202-3414

Close Tolerance Screw - Page 2 of 2



_					
CI	~~	14	I i	ife:	
J.	16			HE.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0