## NSN 5305-01-203-1662



Close Tolerance Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-203-1662 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.425 inches **Fastener Length:** Between 1.853 inches and 1.873 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.455 inches and 0.510 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.250 inches **Grip Length:** Between 1.428 inches and 1.448 inches Thready Qty Per Inch (tpi): 28 **Countersink Angle:** Between 99.0 degrees and 100.0 degrees Material: Steel comp 4340 or steel comp 8740 **Material Specification:** Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams 6322 assn standard 2nd material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

Fiig:

A003b0

## NSN 5305-01-203-1662

Close Tolerance Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-5000 spec.