## NSN 5305-01-203-1663

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-203-1663

Thread Class:	
3a	
Thread Direction:	
Right-hand	
Thread Length:	
0.469 inches	
Fastener Length:	
Between 1.334 inches and	1.354 inches
Head Style:	
Flat countersunk	
Head Diameter:	
Between 0.574 inches and	0.637 inches
Grip Diameter:	
Between 0.3110 inches ar	d 0.3120 inches
Internal Drive Style:	
Cross recess type 1	
Thread Diameter:	
0.312 inches	
Grip Length:	
Between 0.865 inches and	0.885 inches
Thready Qty Per Inch (tp	i):
24	
Countersink Angle:	
Between 99.0 degrees and	d 100.0 degrees
Material:	
Steel comp 4340 or steel	comp 8740
Material Specification:	
Mil-s-5000 military specific	ation 1st material response or mil-s-6049 military specification 2nd material response or ams 6322 assn standard
2nd material response	
Surface Treatment:	
Cadmium	
Surface Treatment Spec	fication:
Qq-p-416 federal specifica	tion single treatment response
Thread Series Designate	r:
Unjf	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A003b0	

## NSN 5305-01-203-1663

Close Tolerance Screw - Page 2 of 2

## Mil-std (military Standard):

Mil-s-5000 spec.

