NSN 5305-01-203-2634

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-203-2634



Thread Class: 3a

Thread Direction:

Right-hand

Thread Length:

Between 1.401 inches and 1.531 inches

Fastener Length:

Between 1.484 inches and 1.531 inches

Head Style:

Hexagon

Head Height:

Between 0.156 inches and 0.171 inches

Width Between Flats:

Between 0.429 inches and 0.439 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.312 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

Between 36.0 rockwell c and 40.0 rockwell c

Screw Material:

Iron alloy 660

Screw Material Specification:

Ams5731 assn standard single material response or ams5737 assn standard single material response

Screw Surface Treatment:

Passivate

Screw Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas1802 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 5305-01-203-2634 Machine Screw - Page 2 of 2

Fiig: A500d0

