NSN 5305-01-204-0970

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-204-0970 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.190 inches **Fastener Length:** Between 0.594 inches and 0.625 inches **Head Style:** Pan **Head Diameter:** Between 0.256 inches and 0.270 inches **Head Height:** Between 0.087 inches and 0.097 inches **First Diameter From Head:** 0.090 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.405 inches **Point Style:** Flat **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 80000 pounds per square inch **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Primer and 2 coats of paint to head only Material: Steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303 plus x or steel comp 303se or steel comp 303cu or steel comp 303ma or steel comp 304 or steel comp 304l **Surface Treatment: Passivate Surface Treatment Specification:**

N/a

Unc

Shelf Life:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

NSN 5305-01-204-0970

Externally Relieved Body Screw - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A003b0