No

Externally Relieved Body Screw - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-01-204-0971

Thread Class:	
2a	
Thread Direction:	
Right-hand	
Thread Length:	
Between 0.200 inches	and 0.215 inches
Fastener Length:	
Between 0.593 inches	and 0.625 inches
Head Style:	
Pan	
Head Diameter:	
Between 0.306 inches	and 0.322 inches
Head Height:	
Between 0.105 inches	and 0.115 inches
First Diameter From H	Head:
Between 0.120 inches	and 0.125 inches
Distance From Large	st Bearing Surface Of Head To End Of First Diameter:
Between 0.378 inches	and 0.425 inches
Point Style:	
Flat	
Internal Drive Style:	
Cross recess type 1	
Thread Diameter:	
0.164 inches	
Thready Qty Per Inch	(tpi):
32	
Externally Relieved B	Body Diameter Quantity:
1	
Material:	
Steel comp 301 or ste	el comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or
steel comp 305 or stee	el comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or
steel comp 316 or stee	el comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel
comp 385	
Surface Treatment:	
Passivate	
Surface Treatment Sp	pecification:
-	ication single treatment response
Thread Series Design	
Unc	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	

## NSN 5305-01-204-0971

Externally Relieved Body Screw - Page 2 of 2

Fiig: A003b0

