NSN 5305-01-204-3300

Machine Screw - Page 1 of 1

View Online at https://aerobasegroup.com/nsn/5305-01-204-3300



Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.5943 inches and 0.6875 inches

Fastener Length:

Between 0.6563 inches and 0.6875 inches

Head Style:

Pan

Head Diameter:

Between 0.256 inches and 0.270 inches

Head Height:

Between 0.087 inches and 0.097 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.138 inches

0.150 1101165

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

75000 pounds per square inch

Screw Material:

Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385 or steil steel comp 316 or steel comp 316 or steel comp 305 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385 or steil steel comp 348 or steel comp 348 or steel comp 384 or steel comp 385 or steel comp 348 or steel comp 348 or steel comp 384 or steel comp 385 or steel comp 348 or steel comp 348 or steel comp 348 or steel comp 348 or steel comp 384 or steel comp 385 or steel comp 348 or steel comp 348 or steel comp 384 or steel comp 385 or steel comp 348 or steel comp 348 or steel comp 384 or steel comp 385 or steel comp 348 or steel comp 348 or steel comp 384 or steel comp 345 or steel comp 348 or steel comp 348 or steel comp 385 or steel comp 348 or steel comp 348 or steel comp 385 or steel comp 348 or steel comp 348 or steel comp 385 or steel comp 348 or steel comp

Screw Surface Treatment:

Passivate

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A500d0