NSN 5305-01-204-3930

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-204-3930



Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.345 inches and 0.438 inches

Fastener Length:

Between 0.407 inches and 0.438 inches

Head Style:

Fillister

Head Diameter:

Between 0.208 inches and 0.226 inches

Head Height:

Between 0.089 inches and 0.096 inches

Hole Diameter:

0.046 inches

Internal Drive Style:

Slot

Thread Diameter:

0.138 inches

Hole Quantity:

1

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

80000 pounds per square inch

Screw Material:

Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384

Screw Surface Treatment:

Cadmium and chromate

Screw Surface Treatment Specification:

Qq-p-416, cl 3 type 2 federal specification single treatment response

Head Hole Configuration Style:

Double hexagon flats

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 5305-01-204-3930

Machine Screw - Page 2 of 2

Fiig: A500d0

