NSN 5305-01-204-3931

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-204-3931

Thread Olever
Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 0.407 inches and 0.500 inches
Fastener Length:
Between 0.469 inches and 0.500 inches
Head Style:
Fillister Head Biometers
Head Diameter:
Between 0.250 inches and 0.270 inches
Head Height:
Between 0.106 inches and 0.113 inches
Hole Diameter:
0.046 inches
Internal Drive Style:
Slot
Thread Diameter:
0.164 inches
Hole Quantity:
1
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
80000 pounds per square inch
Screw Material:
Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384
Screw Surface Treatment:
Cadmium and chromate
Screw Surface Treatment Specification:
Qq-p-416, cl 3 type 2 federal specification single treatment response
Head Hole Configuration Style:
Double hexagon flats
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

NSN 5305-01-204-3931

Machine Screw - Page 2 of 2



Fiig:

A500d0