NSN 5305-01-204-4183

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-204-4183 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.380 inches **Fastener Length:** 1.160 inches **Head Style:** Hexagon **Head Height:** 0.160 inches Width Between Flats: 0.375 inches Point Length: 0.040 inches **First Diameter From Head:** 0.140 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.740 inches Point Style: Cone **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Point Chamfer Angle:** 120.0 degrees **Special Features:** Lusterless green Material: Steel comp 630 **Surface Treatment:** Paint **Surface Treatment Specification:** Mil-c-46168 military specification single treatment response **Thread Series Designator:**

Unf

NSN 5305-01-204-4183

Externally Relieved Body Screw - Page 2 of 2



N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0
Mil-std (military Standard):

Mil-c-46168 spec.

Shelf Life: