

View Online at <https://aerobasegroup.com/nsn/5305-01-204-4682>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.257 inches and 0.312 inches

Fastener Length:

Between 0.301 inches and 0.337 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.096 inches and 0.119 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.060 inches

Thready Qty Per Inch (tpi):

80

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Screw Material:

Steel comp 321 or steel comp 347 or steel comp 302 or steel comp 303

Screw Material Specification:

Qq-s-763 federal specification 1st material response or qq-s-763 federal specification 2nd material response or mil-s-7720 military specification 3rd material response or astm a582 assn standard 4th material response

Screw Surface Treatment:

Passivate

Screw Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unf

Specification Data:

80205-nas662 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-s-7720 spec.