

NSN 5305-01-204-4692 Socket Head Cap Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-204-4692 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 1.400 inches **Fastener Length:** Between 2.670 inches and 2.750 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.735 inches and 0.750 inches **Head Height:** Between 0.492 inches and 0.500 inches **Hole Diameter:** Between 0.061 inches and 0.067 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.500 inches Width Across Flats: Between 0.375 inches and 0.379 inches **Hole Quantity: Hole Type:** Drilled Thready Qty Per Inch (tpi): Min. Tensile Strength (psi):

170000 pounds per square inch

Hardness Rating:

38.0 rockwell c and 45.0 rockwell c

Minimum Yield Strength:

150000 pounds per square inch

**Hole Configuration Style:** 

Round internal hexagon

Material:

Steel

**Material Specification:** 

Ff-s-86 federal specification single material response

**Surface Treatment:** 

Cadmium and chromate

## NSN 5305-01-204-4692

Socket Head Cap Screw - Page 2 of 2



## **Surface Treatment Specification:**

Qq-p-416, type 2, class 2 federal specification single treatment response

**Thread Series Designator:** 

Unrf

**Specification Data:** 

80205-nas1351 professional/industrial association standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0