## NSN 5305-01-204-6837

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-204-6837 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.064 inches and 0.125 inches **Fastener Length:** Between 0.119 inches and 0.155 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.120 inches and 0.146 inches **Locking Feature:** Pellet threads **Internal Drive Style:** Slot **Thread Diameter:** 0.073 inches Thready Qty Per Inch (tpi): **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel comp 321 or steel comp 347 or steel comp 302 **Material Specification:** Qq-s-763 federal specification 1st material response or qq-s-763 federal specification 2nd material response or mil-s-7720 military specification 3rd material response or astm a582 assn standard 4th material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc **Specification Data:** 80205-nas662 professional/industrial association standard Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

Fiig: A003b0

No

## NSN 5305-01-204-6837

Socket Head Cap Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-7720 spec.