NSN 5305-01-205-3409

Machine Screw - Page 1 of 2

Unjf



View Online at https://aerobasegroup.com/nsn/5305-01-205-3409

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 2.460 inches and 2.531 inches
Fastener Length:
Between 2.484 inches and 2.531 inches
Head Style:
Hexagon
Head Height:
Between 0.125 inches and 0.140 inches
Width Between Flats:
Between 0.367 inches and 0.376 inches
Hole Diameter:
Between 0.046 inches and 0.056 inches
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.250 inches
Hole Quantity:
3
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
Between 36.0 rockwell c and 40.0 rockwell c
Product Name:
Navy special project
Screw Material:
Steel comp e4340 or steel comp 8740
Screw Material Specification:
Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams6322 assn standard
2nd material response
Screw Surface Treatment:
Cadmium and chromate
Screw Surface Treatment Specification:
Qq-p-416, ty2, cl2 federal specification single treatment response
Head Hole Configuration Style:
Hexagon corners
Thread Series Designator:

NSN 5305-01-205-3409

Machine Screw - Page 2 of 2



Specification Data:
80205-nas1801 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

A500d0

No **Fiig:**

Mil-std (military Standard):

Mil-s-5000 spec.