NSN 5305-01-205-3414

Thread Class:

За

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-205-3414

| Thread Direction: |
|---|
| Right-hand |
| Thread Length: |
| Between 0.419 inches and 0.500 inches |
| Fastener Length: |
| Between 0.469 inches and 0.500 inches |
| Head Style: |
| Pan |
| Head Diameter: |
| Between 0.205 inches and 0.219 inches |
| Head Height: |
| Between 0.070 inches and 0.080 inches |
| Locking Feature: |
| Strip threads or patch threads or pellet threads |
| Internal Drive Style: |
| Cross recess type 1 |
| Thread Diameter: |
| 0.112 inches |
| Thready Qty Per Inch (tpi): |
| 40 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Hardness Rating: |
| 36.0 rockwell c and 40.0 rockwell c |
| Surface Finish: |
| 32.0 microinches threads |
| Material: |
| Iron alloy 660 |
| Material Specification: |
| Ams5737 assn standard single material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Thread Series Designator: |
| Unjc |
| Olijo |
| Specification Data: |
| |
| Specification Data: |

NSN 5305-01-205-3414

Socket Head Cap Screw - Page 2 of 2



| | | | ure: | |
|--|--|--|------|--|
| | | | | |
| | | | | |

--

Demilitarization:

No

Fiig:

A003b0