

View Online at <https://aerobasegroup.com/nsn/5305-01-205-4984>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 2.750 inches and 3.108 inches

Fastener Length:

Between 1.875 inches and 2.000 inches

Head Style:

Hexagon

Head Height:

Between 0.749 inches and 0.813 inches

Width Between Flats:

Between 1.812 inches and 1.875 inches

Thread Diameter:

1.250 inches

Thready Qty Per Inch (tpi):

7

Min. Tensile Strength (psi):

80000 pounds per square inch

Hardness Rating:

80.0 rockwell b

Minimum Yield Strength:

30000 pounds per square inch

Material:

Steel comp 302 or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 309 or steel comp 310 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 322 or steel comp 324 or steel comp 347

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unc

Specification Or Standard:

2 type and 10p style

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0