
## NSN 5305-01-205-9166

Close Tolerance Screw - Page 1 of 2





**Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** Between 0.298 inches and 0.348 inches Fastener Length: Between 1.058 inches and 1.088 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.325 inches and 0.385 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches Single Shear Strength: 132000 pounds per square inch **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.190 inches Grip Length: Between 0.740 inches and 0.760 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 220000 pounds per square inch Hardness Rating: 46.0 rockwell c and 49.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel comp h11 **Material Specification:** Ams 6487 assn standard single material response Surface Treatment: Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

## NSN 5305-01-205-9166

Close Tolerance Screw - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

