NSN 5305-01-205-9169

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-205-9169 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.381 inches and 0.431 inches **Fastener Length:** Between 0.703 inches and 0.733 inches **Head Style:** Oval countersunk **Head Diameter:** Between 0.2966 inches and 0.3016 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.302 inches and 0.322 inches Thready Qty Per Inch (tpi): 32 **Countersink Angle:** 101.0 degrees Material: Nickel alloy 718 **Material Specification:** 23-118, ty d, fscm 76301 mfr ref single material response **Surface Treatment:** Aluminum and chromate **Surface Treatment Specification:** Mil-c-83488, type 2, cl 3 military specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No Fiig:

A003b0

NSN 5305-01-205-9169

Close Tolerance Screw - Page 2 of 2



Mil-std (military Standard):

Mil-c-83488 spec.