## NSN 5305-01-206-2156

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-206-2156 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.360 inches and 0.400 inches **Fastener Length:** Between 1.230 inches and 1.270 inches **Head Style:** Knurled no. 1 **Head Diameter:** Between 0.745 inches and 0.755 inches **Head Height:** Between 0.230 inches and 0.270 inches **First Diameter From Head:** Between 0.170 inches and 0.180 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.965 inches and 0.975 inches **Point Style:** Cone **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 **Externally Relieved Body Diameter Quantity:** Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5305-01-206-2156

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0