## NSN 5305-01-206-3469

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-206-3469 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.346 inches and 0.438 inches **Fastener Length:** Between 0.408 inches and 0.438 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.262 inches and 0.270 inches **Head Height:** Between 0.159 inches and 0.164 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.164 inches Width Across Flats: Between 0.1406 inches and 0.1426 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 75000 pounds per square inch **Hardness Rating:** 80.0 rockwell b Minimum Yield Strength: 30000 pounds per square inch Material: Steel comp 302 or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 316 **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5305-01-206-3469

Socket Head Cap Screw - Page 2 of 2



Fiig:

A003b0