NSN 5305-01-206-7213



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-206-7213 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 1.126 inches and 1.250 inches **Fastener Length:** Between 1.188 inches and 1.250 inches **Head Style:** Fillister **Head Diameter:** Between 0.292 inches and 0.313 inches **Head Height:** Between 0.123 inches and 0.130 inches **Hole Diameter:** 0.046 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches **Hole Quantity:** Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 80000 pounds per square inch **Screw Material:** Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 **Screw Material Specification:** 66 federal standard all material responses **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416, type 2, class 3 federal specification single treatment response **Head Hole Configuration Style:** Round **Thread Series Designator:** Unf Shelf Life:

N/a

Unit Of Measure:

NSN 5305-01-206-7213

Machine Screw - Page 2 of 2



_					
11	em)	 tor	172	n	

No

Fiig:

A500d0